

MICA HC-41/42 FAST CHARGER TECHNICAL DATA

MODEL	HC FAST CHARGER
Product description	HC-41 single charger HC-42 twin charger Made in Finland by Mica Elektro Oy Ltd.
EMC Certification	Directives 72/245/EEC, 95/54/EC Cert. No. e17*72/245*95/54*0094*00
Charging method	Minus delta V fast charger
Enclosure	High impact Nylon/Aluminium
Input voltage	12VDC
Charging temperature	+5°C...+40°C
Fast charge current	650mA
Trickle charge current	50mA
Recharge time	2h 25 min
Ingress protection	IP 20
Weight	170 g
Dimensions	152 x 115 x 62 mm
Mounting	Wall mounted vertical or horizontal
Compatible headlamp	HL-200, HL-800Ex
Led functions	Green LED power ON (without battery) Green LED fully charged (with battery) Yellow LED fast charge ON (with battery) Yellow LED too low input voltage (without battery) Red LED Charging failure
Charging features	Sophisticated charge and battery protection: Minus delta V cut-off Vmax Cut-off at 7,8V Maximum time cut-off after 3 hrs
Accessories	IL-2 mains adapter CR-15 power supply for max. 5 HC chargers IL-5 changeover unit from car battery Cigarette lighter cable

HC-42 + HB-200



HB-800

