

NM-9000 & NM-4500 Batteries Technical Data

MODEL	NM-9000 and NM-4500 NiMH battery
Product description	9,0Ah & 4,5Ah NiMH batteries for SL- & HL-lamps with JP-plug
Operating temperature	-20°C...+40°C
Ingress protection	IP 65
Weight	NM-9000 1,2 kg - NM-4500 0,8kg
Battery dimensions	180mm (L) x 65mm (W) x 90mm (H) NM-4500: 180 x 65 x 81mm
Battery cells	NiMH 6 V 9,0 Ah (NM-9000) - NiMH 6 V 4,5Ah (NM-4500)
Enclosure	PA 66 polyamide /aluminium
Belt holder	2 pcs spring steel clip, powder coated
Operating time	4 watt halogen = 12 h (battery for halogen lamps is NM-9000) 6 watt halogen = 8 h 10 watt halogen = 5 h 20 watt halogen = 2 h 20min 1W LED = 18 h (with NM-4500 battery)
Chargers	MICA NMC-20 fast table charger MICA NMC-12 standard charger MICA NMCC car charger
Charging time	MICA NMC-20 5,5h/3,0h For NM-9000/NM-4500 MICA NMC-12 9,0h/4,5h Charging temperature +0°C...+40°C MICA NMCC 6,0h/3,0h
Features	<ul style="list-style-type: none"> - Deep discharge prevention - Low battery warning (blinking) - Device short circuit protection with indicator - Steel belt clips - ¼ inch jack-plug connector

NM-9000 & NM-4500 BATTERIES



NMCC



NMC-20



NMC-12

